



# A800

## UNLIMITED POSSIBILITIES



### PRODUCT INFORMATION

Never before has coffee culture been so bursting with vitality, with a greater variety of coffee flavor for individuals to enjoy their own perfect coffee moment than ever before. There are countless ways to reinvent coffee and no end to the surprises in store. Our A800 professional coffee maker was created to produce just such barista coffee. It can perfect any beverage you could possibly imagine.

### KEY FEATURES

- Selection from three different brewing units optimally adjusted to your way of making coffee
- The intuitive 10.4" touchscreen makes operation simple and efficient, and can be configured to your individual requirements
- Functional lighting concept
- Generously sized bean hopper for simple refilling
- Maximum energy efficiency thanks to a timer function and minimal power consumption in Standby mode

### A800 OPTIONS

- Second a/o third bean grinder
- 2x1 kg or 1x2 kg bean hopper, lockable
- One or two separate powder dosing systems (for chocolate or milk powder, lockable)
- SU12: Franke's new 12-liter refrigerator are designed to integrate seamlessly into the system
- Coffee grounds ejector
- Cup sensor
- M2M/telemetry, Billing systems, Raised feet (100 mm)
- Autosteam steam spout (enhanced milk foaming) or Autosteam Pro (automatic milk foaming)
- Colors: gloss black or matt gray

### MILK SYSTEMS

- **FoamMaster™**: hot and cold milk & milk foam, individually adjustable consistency
- FoamMaster integrated in coffee machine
- Hygienic, with container system
- Hose-free docking system for the milk container
- Automated cleaning process with integrated cleaning cartridge
- Conforms to HACCP

### FLAVOR-STATION

- Automatic dosing station for up to three flavors (only with FoamMaster™)

### CUP WARMER

- With four heatable trays

### CAPACITY A800

- Recommended daily output (cups) 150 – 250
- Recommended yearly output (cups) 60 000

### TECHNICAL SPECIFICATION

Electrical connection	Coffee Machine	400 V 3LN PE 50/60Hz 16A, 6.7-7.9kW
	Refrigeration unit*	200-240V 1LN PE 50/60Hz, 100W
	Flavor station	100-240 V 1LN PE 50/60Hz 10A, 75W
Water connection	Supply line	Metal hose with G3/8" union nut, L = 1.5m
	Water pressure	80 to 800 kPa (0.8 to 8.0 bar)
	Water hardness	max 70mg CAO per liter of water (7dH, 13°FH)
	Chloride content	max 0,1 mg/l
	Ideal pH value	7
Dimensions in mm	Coffee Machine	340 x 730 x 600 mm (width x height x depth)
	Refrigeration unit*	340 x 540 x 475 mm (left side of the machine)
	Flavor station	200 x 542 x 451 mm (right side of the machine)

\* Refrigeration unit = SU12



Franke Kaffeemaschinen AG  
 Franke-Strasse 9 · 4663 Aarburg  
 Fon +41 62 78731 31  
 coffe.franke.com

